



CORDEXaqua®
Essential for fishing and marine crafts

"Tying your future today"



CORDEXaqua® POLYTEC

Ropes produced with a mix of Cordsteel and Polyester enabling it to sink.
Ideal combination of breaking strength and abrasion resistance.
Best cost/benefit ratio on a sinking rope.

Ø mm	3 Strands CRL (Kg)	g/m
4	280	10.8
6	500	36.3
8	1000	47
10	1300	60
12	1600	87.2
14	3000	116
16	3900	154.4
18	4200	170

Product properties:

Material:

- Cordsteel (50%)
- Polyester (50%)

Chemical resistance: Good

Specific Gravity (Density): (1,14 - non floating)

Breaking load (wet): Equal dry and wet

Abrasion Resistance: Very Good

UV Resistance: Good

Water Absorption: <0,5%

Construction: 3-4 strands

Melting point: ±165-260° C

Color: Light green

Marker: On request

Maximum Elongation: 8 – 16%

Applications:

- General mooring and towing ropes;
- Off-shore;

- All Ropes manufactured in accordance to ISO and EN standards.
- The values for the breaking load are purely informative and can be changed without prior notice.
- Ropes can be made with other weight if properly specified by the customer.



Rua da Estrada Nova, nº 785 | P.O. Box 15 | 3386-909 Esmoriz - Portugal
phone: +351 256 750 800 | fax: +351 256 754 900
nuno_vito@cordex.com | pedro_vasconcelos@cordex.com

<http://cordexaqua.cordex.com>

www.facebook.com/cordexaqua